DERWENT-ACC-NO:

1996-186583

DERWENT-WEEK:

199619

COPYRIGHT 2006 DERWENT INFORMATION LTD

Method of drilling of small holes in superhard materials - employs monocrystal diamond tip sealed to coaxial metal holder by multicomponent suspension in vacuum and shaped

by laser pulses

INVENTOR: DETCHUEV YU, A; KUDRYAVTSEV, S B ; SANZHARLINSKII, N G

August 27, 1995

PATENT-ASSIGNEE: DETCHUEV YU A[DETCI]

PRIORITY-DATA: 1992RU-0012489 (December 17, 1992)

PATENT-FAMILY:

PUB-NO

PUB-DATE

LANGUAGE

PAGES 003

MAIN-IPC B23B

RU 2042478 C1

051/00

APPLICATION-DATA: PUB-NO

APPL-DESCRIPTOR

APPL-NO

APPL-DATE

RU 2042478C1

N/A

1992RU-0012489

N/A

December 17, 1992

INT-CL (IPC): B23B051/00 ABSTRACTED-PUB-NO: RU 2042478C

BASIC-ABSTRACT:

A diamond drill for machining of small holes in superhard minerals, ceramics and high strength alloys, employs a monocrystal diamond tip joined to a metallic holder by a multicomponent eutectic compound.

The monocrystal diamond tip (1) held in a jig is sealed to the metal holder (3) in an inert medium or vacuum at 1.3 x 10 power minus 2 Pascals by a multicomponent eutectic suspension with a carbide forming component and adhesive (2) over 3-4 minutes and is shaped by <u>laser</u> pulses of 1.06 micron wavelength at 3-10 kilo Hertz and polished.

ADVANTAGE - This increases mechanical strength of drill and permits increasing drilling depth and reducing diameter size to below 0.7 millimetres. Bul. 24/27.8.95

CHOSEN-DRAWING: Dwg.1/1

TITLE-TERMS: METHOD DRILL HOLE SUPERHARD MATERIAL EMPLOY MONOCRYSTAL DIAMOND TIP SEAL COAXIAL METAL HOLD MULTICOMPONENT SUSPENSION VACUUM SHAPE

LASER PULSE

DERWENT-CLASS: P54

SECONDARY-ACC-NO:

Non-CPI Secondary Accession Numbers: N1996-156158

